



TYPICAL SPECIFICATIONS

ELECTROCHEMICAL SYSTEM: ALKALINE MANGANESE DIOXIDE

NOMINAL VOLTAGE: 6.0

MAXIMUM OFF-LOAD VOLTAGE: 6.6

RATED CAPACITY: 150mAh ON $30K\Omega$ TO 3.6V AT 21°C (70°F)

AVERAGE WEIGHT: 0.39 oz (11.0 g)

OPERATING TEMP. RANGE: -20°C TO 54°C (-4°F TO 130°F)

ANSI DESIGNATION: 1414A

TYPICAL USE	LOAD (OHMS)	DAILY PERIOD	END POINT V	MINIMUM AVERAGE DURATION
RATING	27K	24 hr	3.6	620 hr

TYPICAL MPD HOLDER NO. ABH1/2AA, BA1/2AAPC, BC1/2AA, BH1/2AA, BH1/2AAT

SEE MANUFACTURER'S SPECIFICATION SHEET FOR FURTHER INFORMATION.

AWI	DURACELL	EVEREADY	IEC	KODAK	MAXELL	NEDA	PANASONIC	RAYOVAC	SANYO	TOSHIBA	VARTA	OTHER
	PX28A	A544	4LR44	K28A		1414A	4LR44				V4034PX	