



TYPICAL SPECIFICATIONS

ELECTROCHEMICAL SYSTEM: ZINC AIR

NOMINAL VOLTAGE: 9.0

MAXIMUM OFF-LOAD VOLTAGE: 10.8

RATED CAPACITY: 1.1Ah ON 1.1KΩ TO 0.9V AT 21°C (70°F)

AVERAGE WEIGHT: 1.2 oz (33.0 g)

OPERATING TEMP. RANGE: -20°C TO 54°C (-4°F TO 130°F)

ANSI DESIGNATION: 7004Z

TYPICAL USE	LOAD (OHMS)	DAILY PERIOD	END POINT V	MINIMUM AVERAGE DURATION
SMOKE DETECTOR	43K 620 PULSE	BACKGROUND 1 sec/hr, 24 hr/d	7.5	-

TYPICAL MPD HOLDER NO. BA9VPC, BH9VPC, BC9VPC, BH9VW

TYPICAL MPD SNAPS NO. BS6I OR BS6I-MC

SEE MANUFACTURER'S SPECIFICATION SHEET FOR FURTHER INFORMATION.

AWI	DURACELL	EVEREADY	IEC	KODAK	MAXELL	NEDA	PANASONIC	RAYOVAC	SANYO	TOSHIBA	VARTA	OTHER
	DA146	AC146X				7004Z						