



## TYPICAL SPECIFICATIONS

ELECTROCHEMICAL SYSTEM: NICKLE-METAL HYDRIDE OR NICKLE CADMIUM

NOMINAL VOLTAGE: 8.4 OR 7.2

MAXIMUM OFF-LOAD VOLTAGE: 9.0

RATED CAPACITY: 150mAh TO 6.0V

AVERAGE WEIGHT: 1.5 oz (41.0 g)

OPERATING TEMP. RANGE: CHARGE: 0°C TO 50°C (32°F TO 122°F), DISCHARGE: -20°C TO 50°C (-4°F TO 122°F)

ANSI DESIGNATION: 8.4H5 OR 8.4K5

TYPICAL USE	LOAD (OHMS)	DAILY PERIOD	END POINT V	MINIMUM AVERAGE DURATION
RATING				

TYPICAL MPD HOLDER NO. BA9VPC, BH9VPC, BC9VPC, BH9VW  
 TYPICAL MPD SNAPS NO. BS6I OR BS6I-MC

SEE MANUFACTURER'S SPECIFICATION SHEET FOR FURTHER INFORMATION.

AWI	DURACELL	EVEREADY	IEC	KODAK	MAXELL	NEDA	PANASONIC	RAYOVAC	SANYO	TOSHIBA	VARTA	OTHER
	NC1604	NH22				11605	P9R	604		T9R	V7/8H	