



TYPICAL SPECIFICATIONS

ELECTROCHEMICAL SYSTEM: LITHIUM CARBON MONOFLUORIDE

NOMINAL VOLTAGE: 3.0

MAXIMUM OFF-LOAD VOLTAGE: 3.7

RATED CAPACITY: 39mAh ON 30k Ω TO 2.0V AT 21°C (70°F)

AVERAGE WEIGHT: 0.03 oz (.8 g)

OPERATING TEMP. RANGE: -40°C TO 60°C (-40°F TO 140°F)

ANSI DESIGNATION: 5020LB

| TYPICAL USE | LOAD (OHMS) | DAILY PERIOD | END POINT V | MINIMUM AVERAGE DURATION |
|-------------|-------------|--------------|-------------|--------------------------|
| RATING | 30K | 24 hr | 2.0 | 395 hr |

TYPICAL MPD HOLDER NO. BH500

SEE MANUFACTURER'S SPECIFICATION SHEET FOR FURTHER INFORMATION.

| AWI | DURACELL | EVEREADY | IEC | KODAK | MAXELL | NEDA | PANASONIC | RAYOVAC | SANYO | SONY | VARTA | RENATA |
|-----|----------|----------|--------|-------|--------|------|-----------|---------|-------|------|-------|--------|
| | | | BR1225 | | | | BR1225 | BR1225 | | | | |