

**TYPICAL SPECIFICATIONS**

ELECTROCHEMICAL SYSTEM: LITHIUM CARBON MONOFLUORIDE

NOMINAL VOLTAGE: 3.0

MAXIMUM OFF-LOAD VOLTAGE: 3.7

RATED CAPACITY: 70mAh ON $30k\Omega$ TO 2.0V AT 21°C (70°F)

AVERAGE WEIGHT: 0.053 oz (1.5 g)

OPERATING TEMP. RANGE: -40°C TO 85°C (-40°F TO 185°F)

ANSI DESIGNATION: 5000LB

| TYPICAL USE RATING | LOAD (OHMS) | DAILY PERIOD | END POINT V | MINIMUM AVERAGE DURATION |
|--------------------|-------------|--------------|-------------|--------------------------|
| | 30K | 24 hr | 2.0 | 780 hr |

TYPICAL MPD HOLDER NO. BS-3

SEE MANUFACTURER'S SPECIFICATION SHEET FOR FURTHER INFORMATION.

| AWI | DURACELL | EVEREADY | IEC | KODAK | MAXELL | NEDA | PANASONIC | RAYOVAC | SANYO | SONY | VARTA | OTHER |
|-----|----------|----------|--------|-------|--------|--------|-----------|---------|-------|------|-------|-------|
| | | | BR2016 | | | 5000LB | BR2016 | BR2016 | | | | |