



TYPICAL SPECIFICATIONS

ELECTROCHEMICAL SYSTEM: LITHIUM MANGANESE DIOXIDE

NOMINAL VOLTAGE: 3.0

MAXIMUM OFF-LOAD VOLTAGE: 3.7

RATED CAPACITY: 160mAh ON $2.7\text{k}\Omega$ TO 2.0V AT 21°C (70°F)

AVERAGE WEIGHT: 0.116 oz (3.3 g)

OPERATING TEMP. RANGE: -40°C TO 60°C (-40°F TO 140°F)

ANSI DESIGNATION: 5008LC

TYPICAL USE	LOAD (OHMS)	DAILY PERIOD	END POINT V	MINIMUM AVERAGE DURATION
RATING	15K	24 hr	2.0	900 hr

TYPICAL MPD HOLDER NO. BC1/3N

SEE MANUFACTURER'S SPECIFICATION SHEET FOR FURTHER INFORMATION.

AWI	DURACELL	EVEREADY	IEC	KODAK	MAXELL	NEDA	PANASONIC	RAYOVAC	SANYO	TOSHIBA	VARTA	OTHER
	DL1/3N	2L76	CR11108	K58L	4LR44	5008LC			CR1/3N		CR1/3N	GL2-76, LiM110