



TYPICAL SPECIFICATIONS

ELECTROCHEMICAL SYSTEM: LITHIUM MANGANESE DIOXIDE

NOMINAL VOLTAGE: 3.0

MAXIMUM OFF-LOAD VOLTAGE: 3.7

RATED CAPACITY: 1400mAh ON 100Ω TO 2.0V AT 20°C (68°F)

AVERAGE WEIGHT: 0.60 oz (17.0 g)

OPERATING TEMP. RANGE: -40°C TO 60°C (-40°F TO 140°F)

ANSI DESIGNATION: 5018LC

TYPICAL USE	LOAD (OHMS)	DAILY PERIOD	END POINT V	MINIMUM AVERAGE DURATION
RATING	100	24 hr	2.0	45 hr

TYPICAL MPD HOLDER NO. BC2/3AE OR BH2/3A-3

SEE MANUFACTURER'S SPECIFICATION SHEET FOR FURTHER INFORMATION.

AWI	DURACELL	EVEREADY	IEC	KODAK	MAXELL	NEDA	PANASONIC	RAYOVAC	SANYO	SONY	VARTA	OTHER
	ULTRA 123	EL123AP	CR17345	K123LA	CR123	5018LC	CR123A	RL123A-1	CR123A		CR123A	EL123