



## TYPICAL SPECIFICATIONS

ELECTROCHEMICAL SYSTEM: LITHIUM MANGANESE DIOXIDE OR CARBON MONOFLUORIDE

NOMINAL VOLTAGE: 3.0

MAXIMUM OFF-LOAD VOLTAGE: 3.7

RATED CAPACITY: 1400mAh ON 100Ω TO 2.0V AT 20°C (68°F)

AVERAGE WEIGHT: 0.60 oz (17.0 g)

OPERATING TEMP. RANGE: -40°C TO 60°C (-40°F TO 140°F)

ANSI DESIGNATION: 5017LC

| TYPICAL USE | LOAD (OHMS) | DAILY PERIOD | END POINT V | MINIMUM AVERAGE DURATION |
|-------------|-------------|--------------|-------------|--------------------------|
| RATING      |             |              |             |                          |

TYPICAL MPD HOLDER NO. BC2/3AE OR BH2/3A OR BH2/3AT

SEE MANUFACTURER'S SPECIFICATION SHEET FOR FURTHER INFORMATION.

| AWI | DURACELL | EVEREADY | IEC     | KODAK | MAXELL | NEDA   | PANASONIC | RAYOVAC | SANYO | SONY | VARTA  | OTHER |
|-----|----------|----------|---------|-------|--------|--------|-----------|---------|-------|------|--------|-------|
|     | DL2/3A   |          | CR17335 |       |        | 5017LC | CR2/3A    | CR2/3A  |       |      | CR2/3A |       |