



TYPICAL SPECIFICATIONS

ELECTROCHEMICAL SYSTEM:	LITHIUM MANGANESE DIOXIDE
NOMINAL VOLTAGE:	3.0
MAXIMUM OFF-LOAD VOLTAGE:	3.7
RATED CAPACITY:	150mAh ON 15k Ω TO 2.0V AT 21°C (70°F)
AVERAGE WEIGHT:	0.088 oz (2.5 g)
OPERATING TEMP. RANGE:	-40°C TO 60°C (-40°F TO 140°F)
ANSI DESIGNATION:	5003LC

TYPICAL USE	LOAD (OHMS)	DAILY PERIOD	END POINT V	MINIMUM AVERAGE DURATION
RATING	15K	24 hr	2.0	675 hr

TYPICAL MPD HOLDER NO. BS-3 OR BH32T-C

SEE MANUFACTURER'S SPECIFICATION SHEET FOR FURTHER INFORMATION.

AWI	DURACELL	EVEREADY	IEC	KODAK	MAXELL	NEDA	PANASONIC	RAYOVAC	SANYO	SONY	VARTA	OTHER
L12	DL2025	CR2025	CR2025	KCR2025	CR2025	5003LC	CR2025	CR2025	CR2025		CR2025	EA-100CF