



### TYPICAL SPECIFICATIONS

ELECTROCHEMICAL SYSTEM: LITHIUM MANGANESE DIOXIDE

NOMINAL VOLTAGE: 3.0

MAXIMUM OFF-LOAD VOLTAGE: 3.7

RATED CAPACITY: 200mAh ON 15kΩ TO 2.0V AT 21°C (70°F)

AVERAGE WEIGHT: 0.106 oz (3.0 g)

OPERATING TEMP. RANGE: -40°C TO 60°C (-40°F TO 140°F)

ANSI DESIGNATION: 5004LC

TYPICAL USE	LOAD (OHMS)	DAILY PERIOD	END POINT V	MINIMUM AVERAGE DURATION
RATING	15K	24 hr	2.0	1000 hr

TYPICAL MPD HOLDER NO. BA2032, BH32T-C & BU2032SM-HD-G

SEE MANUFACTURER'S SPECIFICATION SHEET FOR FURTHER INFORMATION.

AWI	DURACELL	EVEREADY	IEC	KODAK	MAXELL	NEDA	PANASONIC	RAYOVAC	SANYO	TOSHIBA	VARTA	OTHER
L14	DL2032	CR2032	CR2032	KCR2032	CR2032	5004LC	CR2032	CR2032	CR2032	CR2032	CR2032	EA-2032C