



TYPICAL SPECIFICATIONS

ELECTROCHEMICAL SYSTEM: LITHIUM MANGANESE DIOXIDE

NOMINAL VOLTAGE: 6.0

MAXIMUM OFF-LOAD VOLTAGE: 7.4

RATED CAPACITY: 1400mAh ON 200Ω TO 2.0V AT 20°C (68°F)

AVERAGE WEIGHT: 1.34 oz (38.0 g)

OPERATING TEMP. RANGE: -40°C TO 60°C (-40°F TO 140°F)

ANSI DESIGNATION: 5024LC

TYPICAL USE	LOAD (OHMS)	DAILY PERIOD	END POINT V	MINIMUM AVERAGE DURATION
RATING	200	24 hr/D	4.0	40 hr

TYPICAL MPD HOLDER NO. BH223-L

SEE MANUFACTURER'S SPECIFICATION SHEET FOR FURTHER INFORMATION.

AWI	DURACELL	EVEREADY	IEC	KODAK	MAXELL	NEDA	PANASONIC	RAYOVAC	SANYO	TOSHIBA	VARTA	OTHER
	DL223A	EL223AP	CR-P2	K223LA	CRP2	5024LC	CRP2	PC223A	CR-P2S		CR-P2	223