

**TYPICAL SPECIFICATIONS**

ELECTROCHEMICAL SYSTEM: LITHIUM MANGANESE DIOXIDE

NOMINAL VOLTAGE: 3.0

MAXIMUM OFF-LOAD VOLTAGE: 3.7

RATED CAPACITY: 280mAh ON  $10k\Omega$  TO 2.0V AT  $20^{\circ}\text{C}$  ( $68^{\circ}\text{F}$ )

AVERAGE WEIGHT: 0.141 oz (4.0 g)

OPERATING TEMP. RANGE:  $-40^{\circ}\text{C}$  TO  $60^{\circ}\text{C}$  ( $-40^{\circ}\text{F}$  TO  $140^{\circ}\text{F}$ )

ANSI DESIGNATION: 5011LC

TYPICAL USE	LOAD (OHMS)	DAILY PERIOD	END POINT V	MINIMUM AVERAGE DURATION
RATING	15K	24 hr	2.0	1350 hr

**TYPICAL MPD HOLDER NO. BH2430T-C**

SEE MANUFACTURER'S SPECIFICATION SHEET FOR FURTHER INFORMATION.

AWI	DURACELL	EVEREADY	IEC	KODAK	MAXELL	NEDA	PANASONIC	RAYOVAC	SANYO	TOSHIBA	VARTA	OTHER
L20	DL2430		CR2430			5011LC			CR2430	CR2430	CR2430	