



TYPICAL SPECIFICATIONS

ELECTROCHEMICAL SYSTEM:	LITHIUM MANGANESE DIOXIDE
NOMINAL VOLTAGE:	3.0
MAXIMUM OFF-LOAD VOLTAGE:	3.7
RATED CAPACITY:	550mAh ON 20kΩ TO 2.0V AT 20°C (68°F)
AVERAGE WEIGHT:	0.217 oz (6.2 g)
OPERATING TEMP. RANGE:	-40°C TO 60°C (-40°F TO 140°F)
ANSI DESIGNATION:	5029LC

TYPICAL USE	LOAD (OHMS)	DAILY PERIOD	END POINT V	MINIMUM AVERAGE DURATION
RATING	7.5K	24 hr	2.0	1325 hr

TYPICAL MPD HOLDER NO. BS-2450 OR BU2450SM-JJ-G
 RETAINER NO.: BK-877, BK-5033

SEE MANUFACTURER'S SPECIFICATION SHEET FOR FURTHER INFORMATION.

AWI	DURACELL	EVEREADY	IEC	KODAK	MAXELL	NEDA	PANASONIC	RAYOVAC	SANYO	TOSHIBA	VARTA	OTHER
	DL2450		CR2450			5029LC			CR2450	CR2450	CR2450	