



### TYPICAL SPECIFICATIONS

ELECTROCHEMICAL SYSTEM: ALKALINE MANGANESE DIOXIDE OR CARBON ZINC

NOMINAL VOLTAGE: 1.5

MAXIMUM OFF-LOAD VOLTAGE: 1.65

RATED CAPACITY: 1120mAh ON  $160\Omega$  TO 0.8V AT  $21^\circ\text{C}$  ( $70^\circ\text{F}$ )

AVERAGE WEIGHT: 0.38 oz (10.77 g)

OPERATING TEMP. RANGE:  $-20^\circ\text{C}$  TO  $54^\circ\text{C}$  ( $-4^\circ\text{F}$  TO  $130^\circ\text{F}$ )

ANSI DESIGNATION: 24A, 24AC, 24AP, 24D

TYPICAL USE	LOAD (OHMS)	DAILY PERIOD	END POINT V	MINIMUM AVERAGE DURATION
TAPE, ELECTRONIC GAMES	10	1hr/d	0.9	5.5hr

### TYPICAL MPD HOLDER NO. BCAAAPC

SEE MANUFACTURER'S SPECIFICATION SHEET FOR FURTHER INFORMATION.

AWI	DURACELL	EVEREADY	IEC	KODAK	MAXELL	NEDA	PANASONIC	RAYOVAC	SANYO	TOSHIBA	VARTA	OTHER
	MN2400	E92	LR03	K3A		24A	AM4	824		LR03N	4003	