



## TYPICAL SPECIFICATIONS

ELECTROCHEMICAL SYSTEM: ALKALINE MANGANESE DIOXIDE OR CARBON ZINC

NOMINAL VOLTAGE: 1.5

MAXIMUM OFF-LOAD VOLTAGE: 1.65

RATED CAPACITY: 7800mAh ON 10Ω TO 0.8V AT 21°C (70°F)

AVERAGE WEIGHT: 2.32 oz (65.8 g)

OPERATING TEMP. RANGE: -20°C TO 54°C (-4°F TO 130°F)

ANSI DESIGNATION: 14A, 14AC, 14CD, 14D

TYPICAL USE	LOAD (OHMS)	DAILY PERIOD	END POINT V	MINIMUM AVERAGE DURATION
PORTABLE LIGHTING	3.9	4 min/hr 8 hr/day	0.9	830 min

TYPICAL MPD HOLDER NO. BHCW, BHCL, BHC-2 &amp; BHC-POL

SEE MANUFACTURER'S SPECIFICATION SHEET FOR FURTHER INFORMATION.

AWI	DURACELL	EVEREADY	IEC	KODAK	MAXELL	NEDA	PANASONIC	RAYOVAC	TOSHIBA	SONY	VARTA	OTHER
	MN1400	E93	LR14	KC		14A	AM2	814	LR14N		4014	BA3042/U