



TYPICAL SPECIFICATIONS

ELECTROCHEMICAL SYSTEM: ALKALINE MANGANESE DIOXIDE OR CARBON ZINC

NOMINAL VOLTAGE: 1.5

MAXIMUM OFF-LOAD VOLTAGE: 1.65

RATED CAPACITY: 16500mAh ON 4.7Ω TO 0.8V AT 21°C (70°F)

AVERAGE WEIGHT: 4.73 oz (134.0 g)

OPERATING TEMP. RANGE: -20°C TO 54°C (-4°F TO 130°F)

ANSI DESIGNATION: 13A, 13AC, 13CD, 13D

TYPICAL USE	LOAD (OHMS)	DAILY PERIOD	END POINT V	MINIMUM AVERAGE DURATION
PORTABLE LIGHTING	1.5	4 min/15 min 8 hr/day	0.9	540 min

TYPICAL MPD HOLDER NO. BHDW, BHDL & BHD-2

SEE MANUFACTURER'S SPECIFICATION SHEET FOR FURTHER INFORMATION.

AWI	DURACELL	EVEREADY	IEC	KODAK	MAXELL	NEDA	PANASONIC	RAYOVAC	TOSHIBA	SONY	VARTA	OTHER
	MN1300	E95	LR20	KD		13A	AMI	813	LR20N		4020	BA3030/U